

Hot melt adhesive system



High laying speed with high quality results – these are today's demands. Döllken Profiles offers an extensive range of tried and tested system tools that will optimally satisfy these demands. Döllken Profiles has developed its hot melt adhesive system for the installation of skirtings – fast, neatly and reliably.

Advantages at a glance:

- fast, neat and reliable gluing of skirtings
- Döllken Profiles offers a guaranteed system that will meet installation requirements
- simple handling and easy application
- integrated ball bearing to prevent dripping



Any questions about the product or would you like tips by our pros? Then simply contact us:
Hotline: +49 3643/ 4170-222
or via our App!

**Döllken
Profiles**

we create.
we innovate.

SURTECO GROUP

Product information



The extra long cable (4.5 m) and open times up to 30 seconds for fixation significantly facilitate installation of the skirting.



The HKS18/300 hot melt adhesive is available in two colours (transparent and orange).



The hook nozzle is easy to replace when required.



Suited for installation of the following Döllken Profiles skirtings:

- EP 60/13
- S 60 flex life Top
- S 100 life
- S 66 / 22 flex life
- Cubu series
- TS 60 / 100 life
- C 60 life Top
- C 100 life
- D 60 life Top
- System MD 63
- System SL 48
- Quick MIG
- CSL 70
- USL 60 / USL 60 K
- USL 60 Clip
- RL 10
- HSL 6.8, 10
- TLE 55
- TL 55

Technical data

Glue gun type HKP 220

- Glue gun with 4.5 m power cable
- Cranked nozzle
- Case
- Manual for glue gun

Hot-melt adhesive HKS18/300

- 5 plastic bags of 2 kg each = 10 kg or
- 1 plastic bucket 5 kg = 66-67 glue sticks



Tips by the Pro

Please refer to the relevant Instructions for use for further notes on installation requirements and application.



Find the instructions for use under:
www.doellken-profiles.com
or in the Doellken App



New installation videos at
www.doellken-profiles.com,
in the Doellken App or
on YouTube.

Döllken Profiles GmbH
Stangenallee 3
99428 Nohra b. Weimar
Follow us on  

T: +49 3643 4170 711
F: +49 3643 4170 330
info@doellken-profiles.com
www.doellken-profiles.com